

| Seal-Fast Seal Product Configurations | | PVC/EPDM | EPDM | Silicone | |
|--|-----------|--|--|--|----------------------------------|
| Substrate (Base Material) | | Steel Clip | Steel Wire (Optional: Stainless Steel Wire) | Stainless Steel (Optional: Steel Wire) | |
| Gasket Material | Type | PVC | EPDM | Silicone | FDA Approved Silicone |
| | Durometer | Shore A 65 | Shore A 70 (Optional: 50 and 90) | | Shore A 90 (Optional: 45 and 60) |
| | Color | Black | Black | Black | White |
| Seal Material (Top or Side Bulb) | Type | EPDM | EPDM | Silicone | FDA Approved Silicone |
| | Durometer | Shore A 65 | Sponge Rubber (EPDM) | Shore A 70 (Optional: 45 and 60) | Shore A 60 |
| | Color | Black | Black | Black | White |
| Operating Temperature Range | | Up to 212°F (100°C) | -40°F to 350°F (-40°C to 177°C) | -50°F to 450°F (-45°C to 232°C) | |
| Interior Weatherometer | | | SAE J1885 | | |
| Exterior Weatherometer | | | SAE J1960 | | |
| Low Temperature Flexibility | | | SAE J200 M8BA 708 B13 Z1-6 | | |
| Flame Propagation - Rail & Aero | | | | ASTM C 542, ASTM C1166 | |
| Flammability of Interior Materials (Burn Resistance) - Automotive | | | FMVSS 302 | | |
| Toxicity - Rail & Aero | | | | BSS 7239, ATS 100/ABD0031 ASTM E 662 & METHOD D 2036-91 | |
| Food Service Equipment | | | | FDA Approved White | |
| Fabrications Options | | Factory pre-cut lengths, bulk, or private branded kits | | | |
| RoHS Compliant | | YES | YES | YES | |